

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20151020-E470442  
**Report Reference** E470442-20151009  
**Issue Date** 2015-OCTOBER-20

**Issued to:** Bruel & Kjaer Vibro GmbH  
Leydheckerstr.10  
64293 Darmstadt GERMANY

**This is to certify that representative samples of** PROCESS CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS

“See Addendum page for models”

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 913 – Standard for Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations  
CAN/CSA C22.2 No. 157-92 – Standard for , Intrinsically Safe and Non-incendive Equipment for Use in Hazardous Locations

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20151020-E470442  
**Report Reference** E470442-20151009  
**Issue Date** 2015-OCTOBER-20

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Process Control Equipment for use in Class I, Div. 1, Groups A, B, C and D, and Class II, Div. 1, Groups E, F and G Hazardous Locations

Displacement Sensor System, cat no. ds822.mc, followed by any alphanumeric characters, consisting of sensor ds822.ds, followed by any alphanumeric characters, cable ds822.ec, followed by any alphanumeric characters and oscillator driver ds822.od, followed by any alphanumeric characters, intrinsically safe for use in Class I, Division 1, Groups A, B, C and D and Class II, Division 1, Groups E, F and G hazardous locations when installed in accordance with Brüel and Kjaer Vibro GmbH Control Drawing No. C105711.001.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

